

Technical Product Sheet - Differential



Contact _____

Company _____

Phone _____ Ext _____

Email _____

Address _____

City _____

State _____ Zip _____

Quantity: _____ One Time Recurring

This is a:
new application
replacement for an existing application

Make/Model being replaced _____

Delivery Date Needed _____

Additional information attached? **Y** **N**

What is being measured?

Existing Part Number: _____ *Indicate any changes below.*

New Part Number: Complete all relevant information below.

Reference: Unidirectional Bidirectional

Positive Side Pressure Media _____

Negative Side Pressure Media _____

Full Scale Capacity _____

Max Line Pressure _____

Accuracy Desired _____

Amplifier: Internal In-Line None

Output: 2mV/V 4-20 ma 2-wire

3mV/V 4-20 mA 3-wire

0-5V 0-10V

How often will output signal be sampled? _____

Excitation: 5Vdc 10Vdc 12Vdc 24Vdc

Electrical Termination _____

Orientation of Electrical Termination _____

Output at Zero _____

Operating Temp. _____

Compensated Temp. _____

Material For O-Ring Seal _____

Pressure Connection _____

Ambient Environment _____

Case Pressure If Submerged _____

Overload (% F.S.) _____

Zero/Span Access: None Top Side

Units of Measure _____

Dynamic/Shock Loads Y N

Vibration Resistant Y N

Size Limitations Y N

Use with Signal Conditioner Y N

Shunt Calibration / SIL3 _____

Agency Compliance _____

Calibration Requirements _____

Wiring Requirements _____

Label Requirements _____

Packaging Requirements _____